



SSM - SSM/HP

Forestry tiller for tractors between 150 and 300 HP with a max working depth of 15 inches.

Standard equipment: double side gear type transmission, PTO drive shaft with cam clutch, gearbox with freewheel, hydraulic rear hood. In addition, for the **SSM/HP** model: stronger transmission for tractors up to 300 HP.

Options: hydraulic top link, hydraulic support roller for height adjustment, adjustable dosing blade.



SSM

Model	Tractor HP min	Tractor HP max	PTO rpm	Working width inches	Overall width inches	Weight lbs	Grinding diameter inches (max)	Teeth q.ty/type A+MH
SSM 200	150	250	1000	80	95	6813	15	76A+4MH
SSM 225	170	250	1000	90	105	7364	15	88A+4MH
SSM 250	190	250	1000	100	114	7615	15	102A+4MH

SSM/HP

Model	Tractor HP min	Tractor HP max	PTO rpm	Working width inches	Overall width inches	Weight lbs	Grinding diameter inches (max)	Teeth q.ty/type A+MH
SSM/HP 200	150	300	1000	80	95	6813	15	76A+4MH
SSM/HP 225	170	300	1000	90	105	7364	15	88A+4MH
SSM/HP 250	190	300	1000	100	114	7915	15	102A+4MH

The data refers to the machine without options.



Rotor type SSM



Tooth type A



Side scraper Type MH