



STCH/R - STCH/R/SD

Stone crushers for road construction for tractors between 180 and 300 HP with a max working depth of 6 inches.

Standard equipment: double side transmission, PTO drive shaft with cam clutch, gearbox with freewheel, adjustable skids, hydraulic rear hood, dosing blade mounted on the rear hood, adjustable counter knives. In addition, for the **STCH/R/SD** model: inner plates in Hardox steel, skids with replaceable Hardox sole, ploughshares made of special steel, adjustable three point linkage.

Options: grader blade, hydraulic top link.

Notes: For their correct usage, a creeper gear transmission is recommended.




STCH/R

Model	Tractor HP		PTO rpm	Working width inches	Overall width inches	Weight lbs	Grinding diameter inches (max)	Working depth inches (max)	Teeth q.ty/type STC+STC/SD
	Min	Max							
STCH/R 200	180	300	1000	79	100	9600	20	6	46STC+4STC/SD
STCH/R 225	200	300	1000	88	110	10164	20	6	52STC+4STC/SD
STCH/R 250	220	300	1000	98	120	10670	20	6	58STC+4STC/SD

STCH/R/SD

Model	Tractor HP		PTO rpm	Working width inches	Overall width inches	Weight lbs	Grinding diameter inches (max)	Working depth inches (max)	Teeth q.ty/type STC+STC/SD
	Min	Max							
STCH/R/SD 200	180	300	1000	79	100	9966	20	6	46STC+4STC/SD
STCH/R/SD 225	200	300	1000	88	110	10714	20	6	52STC+4STC/SD
STCH/R/SD 250	220	300	1000	98	120	11484	20	6	58STC+4STC/SD

The data refers to the machine without options.



Rotor type STCH



Tooth type STC



Tooth type STC/SD