



UMH - UMH/S

Forestry mulcher with fixed teeth rotor for tractors between 110 and 350 HP.

Standard equipment: PTO drive shaft with cam clutch, gearbox with freewheel, hydraulic rear hood, adjustable skids, hydraulic top link, self ranging system of the PTO drive shaft/gearbox, pushing frame, possibility to have the rotor equipped with tooth type „A“ or tooth type „C“.

Options: hydraulic pushing frame, special skids to go underground, raker teeth on hydraulic hood.



UMH

Model	Tractor HP		PTO rpm	Working width inches	Overall width inches	Weight with		Grinding diameter inches (max)	Teeth q.ty	
	min	max				type C lbs	type A lbs		type A	type C
UMH 150	110	150	1000	57	78	6000	6700	16	60A+2C/SD	32C+2C/SD
UMH 175	130	150	1000	67	87	6400	7100	16	70A+2C/SD	36C+2C/SD
UMH 200	160	280	1000	76	100	7350	8100	16	78A+2C/SD	40C+2C/SD
UMH 225	180	280	1000	86	110	7744	8500	16	88A+2C/SD	44C+2C/SD
UMH 250	200	280	1000	95	119	8140	8900	16	96A+2C/SD	48C+2C/SD

UMH/S

Model	Tractor HP		PTO rpm	Working width inches	Overall width inches	Weight with		Grinding diameter inches (max)	Teeth q.ty	
	min	max				type C lbs	type A lbs		type A	type C
UMH/S 200	160	350	1000	76	100	7800	8250	16	78A+2C/SD	40C+2C/SD
UMH/S 225	180	350	1000	86	110	8270	8822	16	88A+2C/SD	44C+2C/SD
UMH/S 250	200	350	1000	95	119	8600	9400	16	96A+2C/SD	48C+2C/SD

The data refers to the machine without options.



Rotor type UMM/S "A"



Tooth type A



Tooth type C/SD



Rotor type UMM/S "C"



Tooth type C



Tooth type C/SD