



UMM/EX UMM/EX/DT

Forestry mulcher with fixed teeth rotor for excavators having a weight between 18 and 30 t.

Standard equipment: 63 cc hydraulic motor with check valve, hydraulic hood, adjustable skids, possibility to have the rotor equipped with tooth type "C" or type "Viper".

Options: custom made attachment plate with pins, 90 cc hydraulic motor, kit DT (= double transmission).



UMM/EX

Model	Power HP	Requirements		Excavator weight		Overall width inches	Weight lbs	Grinding diameter inches (max)	Teeth q.ty/type C+C/SD	Teeth q.ty/type Viper
	Min - Max	Flow gal/min Min - Max	Pressure PSI Min - Max	t Min Max						
UMM/EX 125	120 - 160	32 - 37	3500 - 5000	18 - 25	47	3500	12	26+2	28	
UMM/EX 150	120 - 160	32 - 37	3500 - 5000	18 - 25	57	3700	12	32+2	34	

UMM/EX/DT

Model	Power HP	Requirements		Excavator weight		Overall width inches	Weight lbs	Grinding diameter inches (max)	Teeth q.ty/type C+C/SD	Teeth q.ty/type Viper
	Min - Max	Flow gal/min Min - Max	Pressure PSI Min - Max	t Min - Max						
UMM/EX/DT 125	140 - 200	52 - 80	3500 - 5000	18 - 30	47	3500	12	26C+2C/SD	28	
UMM/EX/DT 150	140 - 200	52 - 80	3500 - 5000	18 - 30	57	3700	12	32C+2C/SD	34	

The data refers to the machine without options.



Rotor type UMM/EX



Tooth type C



Tooth type C/SD



Rotor type Viper



Tooth type Viper